

# Aurora Linear Series Projection Light



IP 65 Working Temp: -40°C~55°C Working Humidity: <math>\leq 95\%</math>

## Description


Kingsun Aurora LED Linear Projection Lighting is exclusively designed for landscape architecture lighting, it utilizes the complete extruded aluminum body, together with the tempered glass cover, well actualized the water-proof application in harsh outdoor environments.

The movable mounting bracket, adjustable angle settings and tool-free connection makes it easy for installation and future maintenance, ideal for various architecture lightings.


## Ordering Information

	Name	Model	Power (W)	Qty of LEDs	Beam Angle	Input Voltage	CCT/Color	Control System	Dimension (mm)
	Aurora Linear	WW1L4012	12	36	60°/25×45°	DC24V	1900-6500K R,G,B,Y; RGB	Without / DMX512	L1,000×W36×H63
		WW1L4015	15	48					
	Aurora Linear	WW1L4012	12	36	60°/25×45°	DC24V	1900-6500K R,G,B,Y; RGB	Without / DMX512	L1,000×W36×H51
		WW1L4015	15	48					
	Aurora Linear	WW1L4012	12	36	110°	DC24V	1900-6500K R,G,B,Y; RGB	Without / DMX512	L1,000×W36×H48
		WW1L4015	15	48					

## Light Distribution Curves



Luminous Intensity Unit : cd/klm  
Type V



Luminous Intensity Unit : cd/klm  
Type V

## Dimensional Drawings

